



GAL MAL THREADED FITTINGS

RX Galvanised Malleable Iron threaded fittings are suitable for general purpose low pressure Applications for air and water. Working Pressure is 150 PSI (Flanges are rated to 50 PSI).

These fittings are hot dip galvanised to ISO 1461 standard.

DESCRIPTION			PIPE SIZE								
Hex Nipple	10	15	20	25	32	40	50	65	80	100	150
Red. Bush	10	15	20	25	32	40	50	65	80	100	150
Socket	10	15	20	25	32	40	50	65	80	100	150
Cap	10	15	20	25	32	40	50	65	80	100	
Plug	10	15	20	25	32	40	50	65	80	100	
Bend 90°	10	15	20	25	32	40	50	65	80	100	
Bend 90° M&F	10	15	20	25	32	40	50	65	80	100	
Elbow 90°	10	15	20	25	32	40	50	65	80	100	150
Elbow 45°		15	20	25	32	40	50	65	80	100	
Elbow 90° M&F	10	15	20	25	32	40	50	65	80	100	
Elbow 45° M&F		15	20	25	32	40	50	65	80	100	
Back Nut		15	20	25	32	40	50	65	80	100	
Tee	10	15	20	25	32	40	50	65	80	100	
Cross	10	15	20	25	32	40	50	65	80	100	
Flange	10	15	20	25	32	40	50	65	80	100	
Union Flat Seat		15	20	25	32	40	50	65	80	100	150
Union Brass Seat	10	15	20	25	32	40	50	65	80	100	
GAL STEEL	PIPE SIZE										
Gal Steel Sockets	10	15	20	25	32	40	50	65	80	100	150
Black Steel Sockets	10	15	20	25	32	40	50	65	80	100	150

