



RX RIMS
541 BILSEN ROAD
GEEBUNG QLD 4034
PH: 07 3865 8733
FAX: 07 3865 3488
Email: info@rxplastics.com.au

LILAC SULLAGE HOSE (PRESSURE)

Recommended Use:



For use with reclaimed water when pressure is used, commonly used on concrete trucks, concrete batching plants and quarries etc.

Features:

- ✓ PROUDLY AUSTRALIAN MADE.
- ✓ Excellent U.V. Resistance to withstand extreme Australian conditions.
- ✓ Ribbed outer cover provides superior resistance to abrasion.
- ✓ Conforms to AS / NZS2554 – Class B
- ✓ Working Pressure 1.6mpa / 232 psi
- ✓ Operating temperature -5°C to + 60°C.
- ✓ Lilac ribbed outer cover Printed “WASTE WATER – DO NOT DRINK”
- ✓ Manufactured with a 4:1 pressure safety factor (burst pressure is four times greater than the operating pressure).

Construction:

Inner core Black flexible PVC with smooth finish
Reinforcing High tenacity polyester yarn
Outer cover UV stabilised lilac (purple) PVC with a ribbed finish



Code	Nom I.D.	Working Pressure @ 20° C	Stock Lengths
01SP20X**	20mm	1.6mpa / 232 psi	20m, & 100m
01SP25X**	25mm	1.6mpa / 232 psi	20m, & 100m